

# Trend Fabric

PERFORMANCE POINT	REQUIREMENTS	TEST METHOD
<b>Durability</b>	• Abrasion Resistance	Wyzenbeek Test 60,000+ Double Rubs, Wire Screen 3 lbs. tension, 3 lbs. pressure ASTM-D-3597 (Heavy Duty)
	• Tear Strength	Tongue Test 15 lbs. ASTM-D-2261
	• Tensile Strength	51 lbs. ASTM-D-5034
<b>Dimensional Stability</b>	• Seam Slippage	38 lbs. ASTM-D-434
	• Minimal Shrinkage & Stretching	ASTM-D-3597
<b>Flammability</b>	• Flame Resistant	UFAC Class IA BIFMA F-1-78 Class A California 117 Class, Does not support flame
<b>Cleanability</b>	Washable/Dry-Cleanable	S: Solvent Base Cleaner W: Water Base Cleaner
<b>Colorfastness</b>	• To Crocking (Wet/Dry)	Class 5
	• To light (40 Hrs. Min)	Class 5
	• To Gas Fumes	Class 5

## Specifications:

Style: Trend Fabric

Contents: 100% Olefin

Width: 54" / Weight: 9 oz./Yd. +/-2%

Roll Length: 50 Yd. +/-2%

Cleanability Code: W/S


Backing: Acrylic

## Features:

- Fade resistant, solution dyed yarns.
- Does not build static charges - ideal for computer rooms.
- Resistant to mildew and bacteria - ideal for health-care.
- Non-allergenic.
- Stable, will not shrink in humidity.



2999 Henkle Drive • Lebanon, Ohio 45036  
800.543-0550 • [www.ghent.com](http://www.ghent.com)



Colors shown above are for reference only and do not reflect the true color and woven mix of Trend colors. For accurate color depiction please refer to actual fabric swatches.